





## Renoir 28W DALI

Adjustable projector with adapter for installation on mains voltage track for 28W LED source with high yield and monochromatic emission in Warm or Natural White shades, excellent color rendering CRI >90. Integrated electronic ballast in On/Off or DALI versions. The device is made of die-cast aluminum and thermoplastic material, it allows 330° rotation around the vertical axis and an inclination of 90° in relation to the horizontal plane.

<b>Code</b>	<b>6521-94-456</b>
<b>Type</b>	Track spotlight
<b>Designer</b>	S.T. Fabas Luce
<b>Eancode</b>	8019282547358
<b>Customs tariff</b>	94054239
<b>Color</b>	White
<b>Material</b>	Aluminum frame
<b>IP</b>	IP20
<b>IK</b>	04
<b>Insulation Class</b>	 CL2
<b>Operating ambient temperature</b>	-5°C + 35°C
<b>Years of warranty</b>	3
<b>Item Dimensions</b>	100mm Ø85mm - 0,5kg
<b>Packaging Dimensions</b>	210x210x90mm - 0.6kg
<b>Light Source 1</b>	
<b>Light source</b>	LED Built-in
<b>LED Characteristics</b>	COB
<b>Light Source Lumen</b>	3150 lm
<b>Item Lumen</b>	3008 lm
<b>Color Temperature</b>	Natural white 4000 K
<b>Optics</b>	35°
<b>Minimum CRI</b>	>90
<b>Luminous Flux Maintenance</b>	50.000h L80 B20
<b>Energy Efficiency Class</b>	
<b>Electrical specifications 1</b>	
<b>Input Voltage</b>	220/240V AC 50/60Hz
<b>Total Absorbed Power</b>	28W
<b>Driver</b>	Included
<b>Power Factor</b>	>0,9
<b>Control System</b>	DALI



CE