

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

## **Paca**

Cylindrical aluminum LED spot light with compact dimensions. Indoor use, ceiling mounted. Available in white or black finishing. The recessed central light source allows for a glare reduction, while a second light source lights up the polycarbonate profiles located in the upper and lower parts, creating a particular atmosphere. Suitable for residential and commercial environments.


Code	6581-02-754	
Туре	Ceiling lamp	
Designer	S.T. Fabas Luce	
Eancode	8019282556015	
Customs tariff	94051950	
Color	White	
Material	Metal frame	
IP	IP40	
IK	07	
Insulation Class	CL1	
Operating ambient temperature	+5° +35°	
Years of warranty	2	
Item Dimensions	105mm Ø90mm - 0.49kg	
Packaging Dimensions	100x100x136mm - 0.54kg	
	Light Source 1	Light Source 2
Light source	LED Built-in	LED Built-in
		LLD Duik iii
LED Characteristics	СОВ	SMD
LED Characteristics Light Source Lumen	COB 848 lm	
		SMD
Light Source Lumen	848 lm	SMD
Light Source Lumen Item Lumen	848 lm 825 lm	SMD 486 lm
Light Source Lumen Item Lumen Color Temperature	848 lm 825 lm Warm white 3000K	SMD 486 lm Warm white 3000K
Light Source Lumen Item Lumen Color Temperature Minimum CRI	848 lm 825 lm Warm white 3000K >80	SMD 486 lm  Warm white 3000K >80
Light Source Lumen Item Lumen Color Temperature Minimum CRI	848 lm  825 lm  Warm white 3000K  >80	SMD 486 lm  Warm white 3000K >80
Light Source Lumen Item Lumen Color Temperature Minimum CRI Energy Efficiency Class	848 lm 825 lm Warm white 3000K >80  A F Electrical specifications 1	SMD 486 lm  Warm white 3000K >80











 $\epsilon$