




## Macas

Compact recessed LED spotlight, adjustable. Cylindrical aluminum body. Available in white or black finishing. Can be used for plasterboard ceilings. Installation depth approx. 35 mm. Thanks to its versatility, it is suitable for residential and commercial environments, creating welcoming atmospheres.

|                                      |  |
|--------------------------------------|--|
| <b>Code</b>                          | <b>6587-02-564</b>   |
| <b>Type</b>                          | Recessed lamp  |
| <b>Designer</b>                      | S.T. Fabas Luce  |
| <b>Eancode</b>                       | 8019282555889  |
| <b>Customs tariff</b>                | 94054239   |
| <b>Color</b>                         | Black  |
| <b>Material</b>                      | Aluminum frame   |
| <b>IP</b>                            | IP40   |
| <b>IK</b>                            | 07   |
| <b>Insulation Class</b>              |     |
| <b>Hole dimension</b>                |  44 |
| <b>Operating ambient temperature</b> | +5°C + 35°C  |
| <b>Years of warranty</b>             | 3  |
| <b>Item Dimensions</b>               | 32mm Ø53mm - 0.1kg   |
| <b>Packaging Dimensions</b>          | 105x90x46mm - 0.15kg   |
| <b>Light Source 1</b>                |  |
| <b>Light source</b>                  | LED Included   |
| <b>LED Characteristics</b>           | SMD  |
| <b>Light Source Lumen</b>            | 360 lm   |
| <b>Item Lumen</b>                    | 301 lm   |
| <b>Color Temperature</b>             | Warm white 3000K   |
| <b>Minimum CRI</b>                   | >80  |
| <b>Energy Efficiency Class</b>       |   |
| <b>Electrical specifications 1</b>   |  |
| <b>Input Voltage</b>                 | 220 - 240V AC 50/60 Hz   |
| <b>Total Absorbed Power</b>          | 4W   |
| <b>Driver</b>                        | Included   |

