




Keros Dark IP 65 Plasterboard recess 590x590

Code	6589-24-715
Type	Recessed lamp
Designer	S.T. Fabas Luce
Eancode	8019282558071
Customs tariff	94054239
Color	White RAL 9003
Material	Metal frame
IP	IP65
IK	04
Insulation Class	
Hole dimension	 580X580
Operating ambient temperature	-20°C / +45°C
International standard compliance	EN 60598-1; EN60598-2-2; EN62471 + IEC TR 62778; EN55015; EN61547; EN61000-3-2; EN61000-3-3; EN 50581; EN IEC 63000
Made In	Italy
Cable gland, cable Ø min-max	N°1 PG M20x1.5, Øext. cable: min 7mm - max 12mm
Model	SKOS
Storage ambient temperature	-20°C / +60°C
Item Dimensions	610x610x120mm - 7kg
Packaging Dimensions	650x650x150mm - 8.3kg
	Light Source 1
Light source	Built-in
LED Characteristics	SMD
Light Source Lumen	5861 lm
Item Lumen	4485 lm
Color Temperature	Natural white 4000 K
Optics	Dark light
Minimum CRI	90
SDCM	3-STEP
Photobiological Risk	RG0
Luminous Flux Maintenance	L70 B50 >70000
UGR	<19
Energy Efficiency Class	
	Electrical specifications 1
Input Voltage	220 - 240V AC 0-50/60 Hz
Total Absorbed Power	35W
Through-Wiring	No
Driver	Included
Power Factor	0,95
Control System	DALI
Power Supply Type	Costant Current
Driver Output	350mA
Driver Input	220/240V 0-50/60Hz
Driver Protection	Mains surge 1kV; (L/N - PE) 2kV

