




Keros Dark IP 65 Plasterboard recess 590x590

Code	6707-04-005
Type	Recessed lamp
Designer	S.T. Fabas Luce
Eancode	8019282062424
Customs tariff	94054239
Color	White RAL 9003
Material	Metal frame
IP	IP65
Insulation Class	
Hole dimension	 560x560
Operating ambient temperature	-20°C / +40°C
International standard compliance	EN 60598-1; EN60598-2-2; EN62471 + IEC TR 62778; EN55015; EN61547; EN61000-3-2; EN61000-3-3; EN 50581;
Made In	Italy
Cable gland, cable Ø min-max	N°1 PG M20x1.5, Øext. cable: min 6mm - max 12mm
Model	KEROS IP65
Storage ambient temperature	-20°C / +60°C
Item Dimensions	590x590x93mm - 6,5kg
Packaging Dimensions	650x650x150mm - 7.5kg
Light Source 1	
Light source	Built-in
LED Characteristics	Power LED
Number of LEDs	24
Light Source Lumen	4360 lm
Item Lumen	2839 lm
Color Temperature	Natural white 4000 K
Optics	Dark light
Typical CRI	82
Minimum CRI	80
SDCM	3-STEP
Photobiological Risk	RG0
Luminous Flux Maintenance	L70 B50 >42000
UGR	<19
Energy Efficiency Class	
Electrical specifications 1	
Input Voltage	220 - 240V AC 50/60 Hz
Total Absorbed Power	45W
Through-Wiring	No
Driver	Included
Power Factor	> 0,9
Control System	On/Off
Power Supply Type	Costant Current
Driver Output	500mA
Driver Input	220/240V~ 50/60Hz
Driver Protection	Mains surge 1kV; (L/N - PE) 2kV

