



## Keros IP65 600x600 Recessed clip-in

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6736-04-055</b>  |
| <b>Type</b>                          | Recessed lamp   |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282072003   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | White   |
| <b>Material</b>                      | Metal frame / Clear prismatic diffuser  |
| <b>IP</b>                            | IP65  |
| <b>Insulation Class</b>              |    |
| <b>Operating ambient temperature</b> | -20°C +40°C   |
| <b>Made In</b>                       | Italy   |
| <b>Item Dimensions</b>               | 600x600x75mm - 7,50kg   |
| <b>Packaging Dimensions</b>          | 650x650x150mm - 10.7kg  |
|                                      | <b>Light Source 1</b>   |
| <b>Light source</b>                  | Built-in  |
| <b>LED Characteristics</b>           | Power LED   |
| <b>Number of LEDs</b>                | 24  |
| <b>Light Source Lumen</b>            | 4360 lm   |
| <b>Color Temperature</b>             | Natural white 4000 K  |
| <b>Optics</b>                        | Dark light  |
| <b>Typical CRI</b>                   | 82  |
| <b>Luminous Flux Maintenance</b>     | > 70.000  |
| <b>UGR</b>                           | <19   |
| <b>Energy Efficiency Class</b>       |  |
|                                      | <b>Electrical specifications 1</b>  |
| <b>Input Voltage</b>                 | 220 - 240V AC 50/60 Hz  |
| <b>Total Absorbed Power</b>          | 45W   |
| <b>Driver</b>                        | Included  |
| <b>Power Factor</b>                  | > 0.9   |
| <b>Control System</b>                | DALI  |

