



Zeus 135W

High efficiency floodlight for functional and architectural lighting. Suitable especially for outdoor areas. It has a wide range of optics to meet all design needs. Device made of die-cast aluminum copper free EN AB 44100. Polyester painting QUALICOAT (Class 1), corrosion resistant to salt spray for 28 days, conforms to Standard IEC60092-306. Available in grey color RAL 7040, INOX brackets.

Code	6870-04-024
Type	Outdoor Projector
Designer	S.T. Fabas Luce
Eancode	8019282106142
Customs tariff	94054239
Color	Grey RAL 7040
Material	Aluminum frame
IP	IP65
IK	07
Insulation Class	 CL1
Operating ambient temperature	-20+35°C
Years of warranty	5
Made In	Italy
Item Dimensions	384x123x319mm - 6.9kg
Packaging Dimensions	420x170x420mm - 7.3kg
Light Source 1	
Light source	LED Built-in
LED Characteristics	SMD
Light Source Lumen	18800 lm
Item Lumen	17320 lm
Color Temperature	Natural white 4000 K
Optics	Asymmetric
Minimum CRI	>80
Luminous Flux Maintenance	>60.000h L70 B50
Energy Efficiency Class	
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	132W
Driver	Included
Power Factor	>0,9
Control System	On/Off

