

## Yuma 2

Recessed drive-over ground spotlight with 4 flush lights. Excellent for creating luminous paths. The light, in addition to aiding orientation, creates an evocative path. Resistant to a static load of up to 2500 kg. Application with outer casing supplied. Aluminium structure. Upper front part in AISI 316 stainless steel, embossed matt chrome finishing.

|                                      |                                                                                       |
|--------------------------------------|---------------------------------------------------------------------------------------|
| <b>Code</b>                          | <b>6910-02-024</b>                                                                    |
| <b>Type</b>                          | Step lights                                                                           |
| <b>Designer</b>                      | S.T. Fabas Luce                                                                       |
| <b>Eancode</b>                       | 8019282009894                                                                         |
| <b>Customs tariff</b>                | 94054239                                                                              |
| <b>Color</b>                         | Stainless steel                                                                       |
| <b>Material</b>                      | Stainless steel AISI 316L                                                             |
| <b>IP</b>                            | IP67                                                                                  |
| <b>IK</b>                            | 10                                                                                    |
| <b>Insulation Class</b>              |  CL1 |
| <b>Hole dimension</b>                |  95  |
| <b>Operating ambient temperature</b> | -20°C +35°C                                                                           |
| <b>Years of warranty</b>             | 3                                                                                     |
| <b>Item Dimensions</b>               | 111mm Ø70mm - 0,50kg                                                                  |
| <b>Packaging Dimensions</b>          | 95x95x150mm - 0.6kg                                                                   |
| <b>Light source</b>                  | <b>Light Source 1</b>                                                                 |
| <b>LED Characteristics</b>           | LED Built-in                                                                          |
| <b>Light Source Lumen</b>            | 125 lm                                                                                |
| <b>Item Lumen</b>                    | 9 lm                                                                                  |
| <b>Color Temperature</b>             | Warm white 3000K                                                                      |
| <b>Minimum CRI</b>                   | >80                                                                                   |
| <b>Energy Efficiency Class</b>       |    |
| <b>Input Voltage</b>                 | <b>Electrical specifications 1</b>                                                    |
| <b>Total Absorbed Power</b>          | 220/240V AC 50/60Hz                                                                   |
| <b>Driver</b>                        | 2,8W                                                                                  |
| <b>Control System</b>                | Included                                                                              |
|                                      | On/Off                                                                                |

