




Febe

Circular recessed IP65 appliance with compact dimensions. Body in die-cast aluminum, opal screen. Led 10W Warm and Natural White, white finish. Electronic power supply on/off or dimmable DALI included. Emergency kit on demand. Perfect for general lighting, for wet rooms and for home lighting.

Code	6913-14-956
Type	Recessed lamp
Designer	S.T. Fabas Luce
Eancode	8019282534310
Customs tariff	94054239
Color	White
Material	Metal and polycarbonate frame
IP	IP65
IK	05
Insulation Class	 CL2
Hole dimension	 82
Operating ambient temperature	-10°C +45°C
Years of warranty	3
Made In	Italy
Item Dimensions	58mm Ø90mm - 0,20kg
Packaging Dimensions	110x120x75mm - 0.3kg
Light Source 1	
Light source	LED Built-in
LED Characteristics	COB
Light Source Lumen	1020 lm
Item Lumen	805 lm
Color Temperature	Natural white 4000 K
Optics	Opal
Typical CRI	80
Luminous Flux Maintenance	> 70.000
Energy Efficiency Class	 F
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	10W
Driver	Included
Power Factor	>0,5
Control System	DALI

