


Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it


## Morea


Square recessed IP65 appliance with compact dimensions. Body in die-cast aluminum, opal screen. Led 10W Warm and Natural White, white finish. Electronic power supply on/off or dimmable DALI included. Perfect for general lighting, for wet rooms and for home lighting.

| Code                          | 6914-14-954                   |
|-------------------------------|-------------------------------|
| Туре                          | Recessed lamp                 |
| Designer                      | S.T. Fabas Luce               |
| Eancode                       | 8019282108634                 |
| Customs tariff                | 94054239                      |
| Color                         | White                         |
| Material                      | Metal and polycarbonate frame |
| IP                            | IP65                          |
| IK                            | 05                            |
| Insulation Class              | CL2                           |
| Hole dimension                | 82                            |
| Operating ambient temperature | -10°C +45°C                   |
| Years of warranty             | 3                             |
| Made In                       | Italy                         |
| Item Dimensions               | 88x88x55mm - 0,22kg           |
| Packaging Dimensions          | 115x115x75mm - 0.34kg         |
|                               | Light Source 1                |
| Light source                  | LED Built-in                  |
| LED Characteristics           | COB                           |
| Light Source Lumen            | 1020 lm                       |
| Item Lumen                    | 650 lm                        |
| Color Temperature             | Natural white 4000 K          |
| Optics                        | Opal                          |
| Typical CRI                   | 80                            |
| Luminous Flux Maintenance     | > 70.000                      |
| Energy Efficiency Class       | Î F                           |
|                               | Electrical specifications 1   |
| Input Voltage                 | 220/240V AC 50/60Hz           |
| Total Absorbed Power          | 10W                           |
| Driver                        | Included                      |
| Power Factor                  | >0,5                          |
| Control System                | On/Off                        |
|                               |                               |









(€ ③