

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

Toodle Asymmetrical round recessed

Small round recessed downlight in die-cast aluminum, designed to house COB 11W LEDs with high color rendering CRI> 90. Asymmetrical emission, supplied as standard with an opal diffuser for diffused emission. Ideal for residential lighting, waiting and transit areas. Available in White, Gold and Black finishes. Standard supplied with TRIAC power supply (DALI and Emergency kit on demand).

| Code | 6960-04-360 |
|-------------------------------|-----------------------------|
| Туре | Recessed lamp |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282509813 |
| Customs tariff | 94059900 |
| Color | Black |
| Material | Aluminum frame |
| IP | IP40 |
| IK | 06 |
| Insulation Class | CL2 |
| Hole dimension | 72 |
| Operating ambient temperature | -20°C +45°C |
| Years of warranty | 3 |
| Item Dimensions | 89mm Ø82mm - 0,30kg |
| Packaging Dimensions | 145x125x145mm - 0.45kg |
| | Light Source 1 |
| Light source | LED Built-in |
| LED Characteristics | СОВ |
| Light Source Lumen | 1270 lm |
| Item Lumen | 1070 lm |
| Color Temperature | Natural white 4000 K |
| Optics | Asymmetric |
| Typical CRI | 92 |
| Energy Efficiency Class | E |
| | Electrical specifications 1 |
| Input Voltage | 220/240V AC 50/60Hz |
| Total Absorbed Power | 11W |
| Driver | Included |
| Power Factor | >0,9 |
| Control System | Triac dimmable |





