

Kris

Small square recessed downlight with symmetrical diffused emission. Die-cast aluminum body in version with frame and trimeless, high color rendering LED CRI> 90. Ideal for residential lighting, waiting and transit areas. Available in Black and White finishes. Supplied as standard with TRIAC power supply (DALI and Emergency kit on demand).

Code	6961-03-262
Type	Recessed lamp
Designer	S.T. Fabas Luce
Eancode	8019282510031
Customs tariff	94059900
Color	Black
Material	Aluminum frame
IP	IP40
IK	05
Insulation Class	 CL2
Hole dimension	 105x105
Operating ambient temperature	-20°C +45°C
Years of warranty	3
Item Dimensions	93 (150)x93 (150)x58mm - 0.45kg
Packaging Dimensions	160x160x110mm - 0.6kg
Light Source 1	
Light source	LED Built-in
LED Characteristics	SMD
Light Source Lumen	890 lm
Item Lumen	631 lm
Color Temperature	Warm White 2700K
Optics	Symmetric
Typical CRI	90
Energy Efficiency Class	 E
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	8W
Driver	Included
Power Factor	>0,4
Control System	Triac dimmable

