Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

Millet Recessed frameless

Extruded aluminum profile with cuts every 10 cm., with opal or prismatic polycarbonate diffuser UGR<19. Available in Warm 169lm/W or Natural white 180lm/W temperatures with mid power led 23/Wm. Integrated power supply for On/Off and DALI power supplies, emergency module available on demand.

Code	**6971-64-121**
Type	Light Line Profiles – Recessed frameless
Designer	S.T. Fabas Luce
Eancode	8019282520429
Customs tariff	94054239
Color	Black
Material	Aluminum frame and polycarbonate
IP	IP40
IK	08
Insulation Class	CL1
Hole dimension	52 X L + 20
Operating ambient temperature	-25C° +45C°
Years of warranty	5
Item Dimensions	46x122mm - 2,2/mkg
	Light Source 1
Light source	LED Built-in
LED Characteristics	SMD
Number of LEDs	80 LED/mt
Light Source Lumen	3580 lm/m
Item Lumen	2243 lm/m
Color Temperature	Natural white 4000 K
Optics	Opal
Typical CRI	85
Minimum CRI	80
Luminous Flux Maintenance	>100.000 h L80 B10
Energy Efficiency Class	A↑G C
	Electrical specifications 1
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	23W/ml
Driver	Included
Control System	DALI
Power Supply Type	Costant Current
Driver Output	350mA
Driver Input	220 - 240 VAC 50/60 Hz





CE