





## Rubens 28W

Adjustable floodlight with adapter for installation on a track, mains voltage for 28W LED source with high efficiency available in Warm or Natural White shades. Excellent color rendering with COB REAL COLOR CRI 97. Built-in electronic ballast in On/Off or DALI versions. The luminaire is made of die-cast aluminum and thermoplastic material, it allows a rotation of 350° around the vertical axis and an inclination of 90° with respect to the horizontal plane. Available in white or black in 16°, 21°, 43° optics.

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6974-92-556</b>  |
| <b>Type</b>                          | Track spotlight   |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282527527   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | White   |
| <b>Material</b>                      | Aluminum frame  |
| <b>IP</b>                            | IP20  |
| <b>IK</b>                            | 04  |
| <b>Insulation Class</b>              |    |
| <b>Operating ambient temperature</b> | -20°C +35°C   |
| <b>Years of warranty</b>             | 5   |
| <b>Item Dimensions</b>               | 118mm Ø70mm - 0.59kg  |
| <b>Packaging Dimensions</b>          | 90x210x210mm - 0.74kg   |
| <b>Light Source 1</b>                |   |
| <b>Light source</b>                  | LED Built-in  |
| <b>LED Characteristics</b>           | COB   |
| <b>Light Source Lumen</b>            | 2600 lm   |
| <b>Item Lumen</b>                    | 1930 lm   |
| <b>Color Temperature</b>             | Warm white 3000K  |
| <b>Optics</b>                        | 43°   |
| <b>Typical CRI</b>                   | 97  |
| <b>Minimum CRI</b>                   | 90  |
| <b>Luminous Flux Maintenance</b>     | 50.000h L80 B10   |
| <b>Energy Efficiency Class</b>       |  |
| <b>Electrical specifications 1</b>   |   |
| <b>Input Voltage</b>                 | 220 / 240V AC 50/60 Hz  |
| <b>Total Absorbed Power</b>          | 28W   |
| <b>Driver</b>                        | Included  |
| <b>Power Factor</b>                  | >0,9  |
| <b>Control System</b>                | DALI  |



CE