

## Manet 600x600 recessed

Direct emission ceiling lamp for recessed installation, stand-in or ceiling-mounted with special accessory. Optical compartment in painted metal, UGR<19 microprismatic shield, Mid power LED 40W high yield CRI 90. White finish, Warm and Natural White. Electronic power supply On/Off, dimmable DALI or 0-10V included. Emergency kit on demand. Perfect for lighting offices, open spaces and for general lighting in large areas.

|                                    |                                                                                       |
|------------------------------------|---------------------------------------------------------------------------------------|
| Code                               | 6981-02-055                                                                           |
| Type                               | Recessed lamp                                                                         |
| Designer                           | S.T. Fabas Luce                                                                       |
| Eancode                            | 8019282525431                                                                         |
| Customs tariff                     | 94051190                                                                              |
| Color                              | White                                                                                 |
| Material                           | Metal frame / Clear prismatic diffuser                                                |
| IP                                 | IP40                                                                                  |
| IK                                 | 05                                                                                    |
| Insulation Class                   |  CL2 |
| Operating ambient temperature      | -20°C +45°C                                                                           |
| Years of warranty                  | 5                                                                                     |
| Item Dimensions                    | 595x595x61mm - 3.0kg                                                                  |
| Packaging Dimensions               | 660x615x90mm - 3.8kg                                                                  |
| <b>Light Source 1</b>              |                                                                                       |
| Light source                       | LED Built-in                                                                          |
| LED Characteristics                | SMD                                                                                   |
| Light Source Lumen                 | 5100 lm                                                                               |
| Item Lumen                         | 4113 lm                                                                               |
| Color Temperature                  | Warm white 3000K                                                                      |
| Optics                             | Prismatic                                                                             |
| Minimum CRI                        | >90                                                                                   |
| Luminous Flux Maintenance          | >54.000h L70 B50                                                                      |
| UGR                                | <19                                                                                   |
| Energy Efficiency Class            |  E |
| <b>Electrical specifications 1</b> |                                                                                       |
| Input Voltage                      | 220/240V AC 50/60Hz                                                                   |
| Total Absorbed Power               | 40W                                                                                   |
| Driver                             | Included                                                                              |
| Power Factor                       | > 0.9                                                                                 |
| Control System                     | DALI/Push                                                                             |

