

Manet 300x1200 recessed

Direct emission ceiling lamp for recessed installation, standin or ceiling-mounted with special accessory. Optical compartment in painted metal, UGR<19 microprismatic shield, Mid power LED 40W high yield CRI 90. White finish, Warm and Natural White. Electronic power supply On/Off, dimmable DALI o 0-10V included. Emergency kit on demand. Perfect for lighting offices, open spaces and for generale lighting in large areas.

Code	6981-02-715
Type	Recessed lamp
Designer	S.T. Fabas Luce
Eancode	8019282530541
Customs tariff	94054239
Color	White
Material	Metal frame / Clear prismatic diffuser
IP	IP40
IK	05
Insulation Class	 CL2
Operating ambient temperature	-20°C +45°C
Years of warranty	5
Item Dimensions	1195x295x62mm - 3,00kg
Packaging Dimensions	1122x370x90mm - 3.9kg
Light Source 1	
Light source	Built-in
LED Characteristics	SMD
Number of LEDs	210
Light Source Lumen	5100 lm
Color Temperature	Warm white 3000K
Optics	Prismatic
Typical CRI	> 90
Luminous Flux Maintenance	>54.000h L70 B50
UGR	<19
Energy Efficiency Class	 E
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	40W
Driver	Included
Power Factor	> 0.9
Control System	On/Off

