

## Manet 300x1200 recessed

Direct emission ceiling lamp for recessed installation, standin or ceiling-mounted with special accessory. Optical compartment in painted metal, UGR<19 microprismatic shield, Mid power LED 40W high yield CRI 90. White finish, Warm and Natural White. Electronic power supply On/Off, dimmable DALI o 0-10V included. Emergency kit on demand. Perfect for lighting offices, open spaces and for generale lighting in large areas.

|                                      |                                                                                       |
|--------------------------------------|---------------------------------------------------------------------------------------|
| <b>Code</b>                          | <b>6981-04-765</b>                                                                    |
| <b>Type</b>                          | Recessed lamp                                                                         |
| <b>Designer</b>                      | S.T. Fabas Luce                                                                       |
| <b>Eancode</b>                       | 8019282530534                                                                         |
| <b>Customs tariff</b>                | 94054239                                                                              |
| <b>Color</b>                         | White                                                                                 |
| <b>Material</b>                      | Metal frame / Clear prismatic diffuser                                                |
| <b>IP</b>                            | IP40                                                                                  |
| <b>IK</b>                            | 05                                                                                    |
| <b>Insulation Class</b>              |  CL2 |
| <b>Operating ambient temperature</b> | -20°C +45°C                                                                           |
| <b>Years of warranty</b>             | 5                                                                                     |
| <b>Item Dimensions</b>               | 1195x295x62mm - 3,00kg                                                                |
| <b>Packaging Dimensions</b>          | 1122x370x90mm - 3.9kg                                                                 |
| <b>Light Source 1</b>                |                                                                                       |
| <b>Light source</b>                  | Built-in                                                                              |
| <b>LED Characteristics</b>           | SMD                                                                                   |
| <b>Number of LEDs</b>                | 210                                                                                   |
| <b>Light Source Lumen</b>            | 5500 lm                                                                               |
| <b>Color Temperature</b>             | Natural white 4000 K                                                                  |
| <b>Optics</b>                        | Prismatic                                                                             |
| <b>Typical CRI</b>                   | > 90                                                                                  |
| <b>Luminous Flux Maintenance</b>     | >54.000h L70 B50                                                                      |
| <b>UGR</b>                           | <19                                                                                   |
| <b>Energy Efficiency Class</b>       |  D |
| <b>Electrical specifications 1</b>   |                                                                                       |
| <b>Input Voltage</b>                 | 220/240V AC 50/60Hz                                                                   |
| <b>Total Absorbed Power</b>          | 40W                                                                                   |
| <b>Driver</b>                        | Included                                                                              |
| <b>Power Factor</b>                  | > 0.9                                                                                 |
| <b>Control System</b>                | 0-10V                                                                                 |

