

Skilos

Skilos recessed for plasterboard false ceilings is a lighting fixture with a 600x600mm modular structure. Provided with an optical system which allows excellent visual comfort, the microprismatic screen guarantees a UGR<19 factor. Equipped with the latest generation of very high efficiency LEDs, 4000K natural light, CRI 90. The IP65 protection degree is guaranteed both on the visible side and on the recessed side. Particularly suitable for operating, aseptic, chemical and food premises. Possibility to have custom-made dimensions.

Code	6524-24-715
Type	Lampe encastrée
Designer	S.T. Fabas Luce
Code Barres	8019282552772
Tarif douanier	94054239
Couleur	Blanc
Matériel	Structure métallique / Diffuseur transparent prismatique
IP	IP65
IK	04
Classe d'isolation	 CL1
Operating ambient temperature	-20°C +45°C
Ans de garantie	5
Dimensions de la lampe	610x610x120mm - 7.0kg
Dimensions de la boîte	650x650x150mm - 8.3kg
Source de lumière 1	
Source	LED Intégré
Caractéristiques des LEDs	SMD
Lumens de la source lumineuse	5861 lm
Lumen de l'article	4485 lm
Température de couleur	Natural white 4000 K
Optique	Prismatique
CRI minimum	>90
UGR	<19
Classe énergétique	 A ↑ G C
Spécifications électriques 1	
Tension d'alimentation	220/240V AC 50/60Hz
Puissance totale absorbée	35W
Driver	Inclus
Facteur de puissance	> 0.9
Système de contrôle	DALI/Push/On-Off

